

7-in-1 Wire Stripper and Crimper

- Strips insulation off electrical wires ranging from 10 AWG—22 AWG (0.6mm—2.6mm) in diameter. Pliers on tip of jaw for looping or grabbing wire in tight places.
- Heat-treated steel jaws cut solid or multi-strand wire.
- Screw cutter shears screws clean, with no thread clean-up required. Works on machine screw sizes 4-40, 5-40, 6-32, 8-32, 10-24, and 10-32.
- Crimps insulated and non-insulated wire terminals, 7mm—8mm spark plug wire connectors.



No. 4498 – 7-in-1 Wire Stripper and Crimper.

Adjustable Oil Filter Pliers

- Forged jaws with sure-grip teeth grab the filter for easy removal.
- Slip-joint ratchet and lock mechanism allows a secure grip on filters.



No. 4560 – Small Adjustable Oil Filter Pliers. Pliers is 13-1/2" long and fits filters ranging from 2-1/4" to 5" (57 mm to 127 mm) in diameter.

No. 4561 – Large Adjustable Oil Filter Pliers. Pliers is 18" long and fits filters ranging from 3-3/4" to 7" (95 mm to 178 mm) in diameter.

No. 4562 – Adjustable Oil Filter Pliers Set. Includes both the No. 4560 and No. 4561 listed above.

Ratcheting Terminal Crimper

- Heavy-gauge steel crimping tool designed for insulated wire terminals.
- Ratcheting action crimps terminal to correct tightness on the wire, making crimping fast and easy.
- For wire sizes: AWG 22–18 (0.6 mm–1.0 mm) red terminal; AWG 16–14 (1.3 mm–1.6 mm) blue terminal; AWG 12–10 (2.0 mm–2.6 mm) yellow terminal.
- Insulated handles with compound mechanical leverage for power.



No. 4497 – Ratcheting Terminal Crimper.

Heavy-Duty Oil Filter Wrenches

- Features a 1/2" wide steel band that can stand up to the high torque needed to remove filters from trucks, tractors, and other heavy equipment.
- Use with a 1/2" drive ratchet or breaker bar.



No. 4555 – Heavy-Duty Oil Filter Wrench for filter diameters of 4-1/8" to 4-21/32" (104 mm to 118 mm).

No. 4556 – Heavy-Duty Oil Filter Wrench for filter diameters of 4-21/32" to 5-5/32" (118 mm to 131 mm).

No. 4557 – Heavy-Duty Oil Filter Wrench for filter diameters of 5-5/32" to 5-21/32" (131 mm to 144 mm).

Angle-Tip Relay Pliers

- Designed to remove and install relays, which are usually located in confined, hard-to-reach areas.
- Specially coated tips offer a solid grip on the relay.



No. 4493 – Angle-Tip Relay Pliers.

Truck Brake Spring Pliers

- Designed to remove and install the brake shoe return springs on medium-duty and heavy-duty drum brakes.



No. 4592 – Truck Brake Spring Pliers.

Interchangeable Punch and Chisel Set


- Safety protective handle allows easy grip and protects hand from being hit by hammer.
- 12 punches and chisels:
 - 1 cape chisel:** 1/4" wide blade
 - 5 flat chisels:** 1/2", 5/8", 3/4", 7/8", and 1" wide blades
 - 2 taper punches:** 1/8" and 1/4" diameter
 - 2 pin punches:** 3/16" and 1/4" diameter
 - 2 center punches:** 1/8" and 3/16" diameter
- Double-locking ball detent holds punch or chisel securely in the driver handle.



No. 4605 – Interchangeable Punch & Chisel Set.

Snap-Style Oil Filter Wrench

- Fits filter diameters up to 6" (152.4 mm).
- Features a strong, nylon strap that won't slip off the filter.
- Use with a 1/2" drive ratchet or breaker bar.



No. 4577 – Snap-Style Oil Filter Wrench.

3-Leg Oil Filter Wrench

- Fits filter diameters ranging from 2-1/2" to 5-1/4" (65 mm to 135 mm).
- Knurled legs provide extra gripping power.
- To turn the tool, use a 1/2" drive ratchet in the ratchet drive or a 13/16" wrench on the nut.



No. 4568 – 3-Leg Oil Filter Wrench.